

SUMIMARK™

SM3 and SM3 Super Ribbons

Applications:

- Heat shrink tubing identification

Product Features:

- Superior resistance to solvents
- Excellent abrasion resistance
- Excellent heat resistance
- Anti-static coating extends print head life

Colors:

SM3 - black, white standard
SM3 Super Ribbon - black only
Colors available with MOQ

Dimensional:

SM3 - 2" and 3.25" width
SM3 Super - 1.5", 2", 3.25" widths
1,000 ft length




Print Performance:

Adherence: SAE-AS5942
MIL-STD-202G, Method 215
Outgassing - NASA SP-R-0022A

Storage and Use Conditions:

Store in original packaging
Temperature - 10°C to 26°C
Avoid temperatures above 40°C
Humidity - 10% to 85% RH
Light - avoid direct sunlight



Product Overview

Quality Counts! Sumimark SM3 and SM3 Super Ribbons have been thoroughly tested to ensure optimal print quality and mark permanence when used in conjunction with the full line of Sumimark IV PLUS Marking System and Sumimark SM3 and Sumitag heat shrink tubing products. For best results with Sumitag products, use SM3 Super Ribbon.

How can we help? Contact us for more information:

800 758 3515
customerservice@seipusa.com
www.seipusa.com

SUMIMARK™

SM3 and SM3 Super Ribbons

SM3 Ribbon

Sumimark SM3, Black 2" (176-20013)

Sumimark SM3, Black 3.25" (176-20001)

Sumimark SM3, White 2" (176-20017)

Sumimark SM3, White 3.25" (176-20016)

Industry Approvals

RoHS compliant

REACH complaint

Technical Specifications

Ink side out

Pigmented resin

Thermal resistant back coated

Recommended Tubing

Sumimark SM3 heat shrink tubing

SM3 Super Ribbon

Sumimark SM3 Super Ribbon, Black 1.5" (176-2002)

Sumimark SM3 Super Ribbon, Black 2" (176-20021)

Sumimark SM3 Super Ribbon, Black 3.25" (176-20010)

Industry Approvals

RoHS compliant

REACH complaint

Technical Specifications

Ink side out

Wax-Resin

Heat

Heat resistant up to 160°C for 5 mins and up to 120°C for 10 days

Recommended Tubing

All Sumitag products and Sumimark SM-CM

We can help: 800 758 3515 customerservice@seipusa.com www.seipusa.com