

Rapid reference



Sumitag[™] BB-E5 Marking System

sumitag

Applications:

• Wire identification

Product Features:

- Prints on 2:1 and 3:1 shrink ratios
- Compatible with Sumitag[™] con-
- tinuous and formatted products
- Optional full or perforated cutter available
- Prints on material diameters from 3/32" to 1"
- Marks on all colors, including clear
- Full networking capabilities

Required Ribbon & Software:

Software - Sumilabel™ Ribbon - Sumimark™ Super Ribbon

Print Performance:

Adherence: SAE-AS5942 MIL-STD-202G, Method 215

Print Specifications:

Print Resolution - 300 DPI Print Speed - Up to 6 IPS Print Width - 4.25" maxiumum Print Length - 450" maximum

Description and Part Number: Sumitag™ BB-E5 S10-10039

sum1tag STP 300 BB-E5

Economical Compact

Product Overview

Quality Counts! The Sumitag[™] BB-E5 thermal transfer printer is an economical option for lower volume printing operations, yet provides excellent print definition and mark permananece on all Sumitag[™] heat shrink products. The compact design is a perfect fit for confined work areas.

Lower Cost! When using Sumitag™ continuous products, the Sumitag[™] BB-E5 significantly lowers total installed cost vs. formatted tubing.


How can we help? Contact us for more information:

800 758 3515 customerservice@seipusa.com www.seipusa.com

©2022 Sumitomo Electric Interconnect Products, Inc. All rights reserved. The Sumitomo Electric logo is a registered trademark of Sumitomo Electric Industries. Other products and brand names may be tradetime of publishing. Specifications given in this publication are subject to change without notice

Sumitomo Electric Interconnect Products, Inc. 915 Armorlite Drive, San Marcos, CA 92069 World leaders in identification and heat-shrink technology

Page 1 of 2











Product insight	Sumitag™ BB-E5	Page 2 of 2
	Marking System	
Consumable Parts	Ribbons:	
	Sumimark™ SM3 Super Ribbon, Black 1.5" (176-2002) Sumimark™ SM3 Super Ribbon, Black 2" (176-20021)	
	Sumimark™ SM3 Super Ribbon, Black 3.25" (1	
	Colors - available upon request, with MOQ	
	Cutter: Cutter, Sumitag BB-E5. (S10-10034)	
	Other:	
	Platen - Sumitag BB-E5 Platen. (S10-10043)	
	Print Head - Sumitag BB-E5 Print Head 300[)PI. (S10-10041)
Electrical	Input - 100-240VAC, 50/60Hz LCD Display	
	Multi-Function Push Button Controls	
Connectivity Interface	Ethernet	
	USB Host - 2 Ports	
Sensors	Gap transmissive	
	Black mark reflective	
	Ribbon end	
	Head open	
Physical Dimensions	Exterior - 10.5"W x 16"D x 9.5"H	
	Weight - 11lbs	
Approvals	CE, FCC Class A, ICES-3, cULus, CB, CoC Mexico, C	CC, EAC, BIS, BSMI,
	KC-Mark	

We can help: 800 758 3515 customerservice@seipusa.com www.seipusa.com

©2022 Sumitomo Electric Interconnect Products, Inc. All rights reserved. The Sumitomo Electric logo is a registered trademark of Sumitomo Electric Industries. Other products and brand names may be trademarks of their respective owners. The information on this datasheet is believed to be correct a the time of publishing. Specifications given in this publication are subject to change without notice

Sumitomo Electric Interconnect Products, Inc. 915 Armorlite Drive, San Marcos, CA 92069 World leaders in identification and heat-shrink technology