



the global cable identification system



### Recommended Ribbon:

SM3 Super Ribbon

### Print Performance:

Adherence: SAE-AS5942

Fluid Resistance: MIL-STD-202 Method 215J

Store in original packaging

Recommended temp. at +10°C to 25°C 45-55% R.H.

Use within 3 years from date of manufacture

## Sumitag™ STP-300 DS-XT Double Sided Thermal Transfer Printer

### Product Overview:

---

The Sumitag™ STP-300 DS-XT double sided printer offers high volume simultaneous printing of high performance two-sided heatshrink sleeves. This robust thermal transfer printer is manufactured for industrial applications and offers excellent print definition and mark permanence. No extra processes of rewinding and reprinting are required. A time-saving solution for wire marking where waste and labeling error is greatly reduced.

---

### Product Features:

- Compatible with all Sumitag™ products
  - Time saving one pass operation
  - Auto positioning for fast media change
  - Ethernet or USB communication interfaces
- 

### Technical Specifications:

Print Resolution	300 dpi
Print Speed	1"-5" per second
Print Width	4.25"
Media Width	3/32" - 2"

## SUMITOMO ELECTRIC INTERCONNECT PRODUCTS, INC.

---

915 Armorlite Drive  
San Marcos, CA 92069-1440

t: 800.758.3515  
f: 800.758.3517  
e: [customerservice@seipusa.com](mailto:customerservice@seipusa.com)  
w: [www.seipusa.com](http://www.seipusa.com)