



Rapid reference Page 1 of 2















Sumitag[™] **SS-SX** Marking System

Applications:

• Wire identification

Product Features:

- Prints on 2:1, 3:1 and 4:1 shrink ratios
- Compatible with all Sumitag[™] continuous and formatted products
- Optional full or perforated cutter available
- Prints on material diameters from 1/16" to 1.5"
- Marks on all colors, including clear
- Full networking capabilities



High Volume Versatile

Required Ribbon & Software:

Software - Sumilabel™ Ribbon - Sumimark™ Super Ribbon

Print Performance:

Adherence: SAE-AS5942 MIL-STD-202G, Method 215

Print Specifications:

Print Resolution - 300 DPI Print Speed - Up to 12 IPS Print Width - 4.25" maximum Print Length - 450" maximum

Description and Part Number:

Sumitag™ SS-SX S10-10012

Product Overview

Quality Counts! The SumitagTM SS-SX thermal transfer printer is a perfect fit for high volume printing operations, while providing excellent print definition and mark permananece on all SumitagTM heat shrink products. Ease of use and intuitive operation are major design features.

Lower Cost! When using SumitagTM continuous products, the SumitagTM SS-SX significantly lowers total installed cost vs. formatted tubing.

How can we help? Contact us for more information:

800 758 3515 customerservice@seipusa.com www.seipusa.com





Product insight

Sumitag™ SS-SX Marking System

Page 2 of 2

Consumable Parts

Ribbons:

Sumimark™ SM3 Super Ribbon, Black 1.5" (176-2002)

Sumimark™ SM3 Super Ribbon, Black 2" (176-20021)

Sumimark™ SM3 Super Ribbon, Black 3.25" (176-20010)

Colors - available upon request, with MOQ

Cutter:

Partial Cutter, Sumitag SS-SX. (S10-10017)

Full Cutter, Sumitag SS-SX. (S10-10016)

Other:

Platen - Sumitag SS-SX Platen. (S10-10009)

Print Head - Sumitag SS-SX Print Head 300DPI. (S10-10015)

Electrical Input - 100-240VAC, 50/60Hz

LCD Display

Multi-Function Push Button Controls

Connectivity Interface Ethernet

USB Host - 3 Ports

Sensors Gap transmissive

Black mark reflective

Ribbon end

Head open

Physical Dimensions Exterior - 10"W x 18"D x 11.5"H

Weight - 22lbs

Approvals CE, FCC Class A, ICES-3, cULus, CB, CoC Mexico, CCC, EAC, BIS, BSMI,

KC-Mark

We can help: 800 758 3515 customerservice@seipusa.com www.seipusa.com