



SumiMark IV PLUS

High Performance Thermal Transfer Printer



Product Overview:

The SumiMark IV PLUS thermal transfer printer is manufactured for industrial applications requiring consistent accuracy, print quality and reliability. It is designed to print on SumiMark continuous and Sumitag formatted heat shrink tubing products.

EASY TO USE – COST EFFECTIVE – FLEXIBLE

Recommended Ribbon:

Ribbon - SM3 Black & White 2" & 3.25" Width
SM3 Super Black

Print Performance:

Adherence - SAE-AS5942
Fluid Resistance - MIL-STD-202G, Method 215J

Product Features & Benefits:

- Integrated cutter for full or partial cutting to customer lengths for maximum cost savings.
- Prints on material diameters from 1/16" to 2", providing greatest flexibility of material widths.
- Prints on 2:1, 3:1 and 4:1 shrink ratios.
- Prints on all colors, including clear and adhesive lined products.
- Ethernet and USB communication for networking capabilities.

Technical Specifications:

Print Resolution	300 Dots Per Inch
Print Speed	Up to 12 Inches per Second
Print Width	4" Maximum
Print Length	14" Maximum

 **SUMITOMO ELECTRIC INTERCONNECT PRODUCTS**

T: 800.758.3515

W: www.seipusa.com

SUMITOMO
ELECTRIC
GROUP