



## SUMIMARK™ IV PLUS Marking System

### Applications:

- Wire identification

### Product Features:

- Integrated cutter for full or partial cutting to length
- Prints on material diameters from 1/16" to 2"
- Prints on 2:1, 3:1 and 4:1 shrink ratios and adhesive lined tubing
- Marks on all colors, including clear
- Full networking capabilities

### Required Ribbon & Software:

Software - Sumilabel™

Ribbon - Sumimark™ SM3

### Print Performance:

Adherence: SAE-AS5942

MIL-STD-202G, Method 215

### Print Specifications:

Print Resolution - 300 DPI

Print Speed - Up to 12 IPS

Print Width - 4" maximum

Print Length - 450" maximum

### Description and Part Number:

Sumimark™ IV PLUS

191-78700



FLEXIBLE APPLICATION  
COST EFFECTIVE  
EASY TO USE

### Product Overview

**Quality Counts!** The Sumimark™ IV PLUS thermal transfer printer is the only on the market designed specifically for marking and cutting Sumimark™ and Sumitag™ heat shrink tubing. The Sumimark IV™ PLUS is manufactured for industrial applications requiring maximum flexibility of applications, ease of use, print quality and reliability.

**Lower Cost!** Due to optimized design for use with continuous tubing, the Sumimark™ IV PLUS significantly lowers total installed cost vs. formatted tubing.

**How can we help?** Contact us for more information:

800 758 3515

customerservice@seipusa.com

www.seipusa.com

## SUMIMARK™ IV PLUS Marking System

### Consumable Parts

#### Ribbons:

- Sumimark™ SM3, Black 2" (176-20013)
  - Sumimark™ SM3, Black 3.25" (176-20001)
  - Sumimark™ SM3, White 2" (176-20017)
  - Sumimark™ SM3, White 3.25" (176-20016)
  - Sumimark™ SM3 Super Ribbon, Black 1.5" (176-2002)
  - Sumimark™ SM3 Super Ribbon, Black 2" (176-20021)
  - Sumimark™ SM3 Super Ribbon, Black 3.25" (176-20010)
- Colors - available upon request, with MOQ

#### Cutter Blades and Block:

- SM3&4 Cutter Blade - No Notch. For full cuts. (191-10025)
- SM3&4 Cutter Blade - Triple Notch. Perf cuts. (191-10041)
- SM3&4 Cutting Block - (191-10037)

#### Other:

- Platen - SM4 PLUS Platen. (191-20002)
- Print Head - SM4 PLUS Print Head 300DPI. (191-70001)

### Electrical

- Input - AC 100-240V, 4-2A, 50-60Hz
- LCD Display
- Multi-Function Push Button Controls

### Connectivity Interface

- Ethernet
- USB Host - 2 Ports
- RS-232

### Sensors

- Gap transmissive
- Black mark reflective
- Ribbon end
- Head open
- Media near end

### Physical Dimensions

- Exterior - 10.9" W x 19.8"D x 12.8"H
- Weight - 37lbs

**We can help:** 800 758 3515    [customerservice@seipusa.com](mailto:customerservice@seipusa.com)    [www.seipusa.com](http://www.seipusa.com)