

SAFETY DATA SHEET

1/3

Ref. No. : M-4G6A

Revised: June 27, 2019

1. Chemical product and company identification

Product name : SUMITUBE AN25

Supplier : Sumitomo Electric Fine Polymer, Inc. (SFP)

950,1-chome, Asashiro nishi, Kumatori-Cho, Sennan-Gun, Osaka, 590-0458, JAPAN

(Tel) 072-452-7192, (Fax) 072-452-7195

Emergency Tel. No.: For SFP subsidiary company

Sumitomo Electric Interconnect Products, Inc.

915 Armorlite Drive, San Marcos, CA 92069, U.S.A.

(Tel) 760-761-0600, (Fax) 760-761-0620

Sumitomo Electric Schrumpf-Produkte GmbH

Oststrasse 89, D-22844 Norderstedt, Germany

(Tel) 40-526-5010, (Fax) 40-526-4808

Sumi-Pac Corporation

8th Fl. No.34, Chung Shann, North Road Section 3.,Taipei 104, Taiwan R.O.C.

(Tel) 2-2599-7382, (Fax) 2-2599-7377

Sumitomo Electric Fine Polymer (Suzhou) Ltd. China(SFPZ)

No.232 Jinfeng Road, Suzhou New District,Suzhou, Jiangsu, 215129 China

(Tel) 512-8918-6680, (Fax) 512-8918-6686

Or for a local distributor

(Name)

(Address)

(TEL/Fax)

2. Hazards identification

GHS classification

Physical hazards: Not applicable

Health hazards:Not applicable

Environmental hazards:Not applicable

Other hazards: If the product is overheated or burned, harmful vapors may be formed.

The heated product has the potential to cause thermal burns, if touched.

<Note> During heating process, a slight characteristic odor of plastic may be noticed. This odor is not harmful.

3. Composition/ Information on ingredients

Substance/Preparation : Preparation

Common name : Irradiated cross-linked, fluid resistant, flame-retardant, flexible elastomer tubing

4. First aid measures

Inhalation : If vapors from the burning or overheated product are inhaled, provide fresh air. If symptoms are not reduced, seek medical advice.

Skin contact: If the heated product contacts skin, remove the product immediately. If there is evidence of reddening or burn, seek medical advice.

Eye contact : If the heated product contacts eyes, rinse thoroughly with plenty of water for at least 15 minutes and seek medical advice.

Ingestion : Seek medical advice.

SAFETY DATA SHEET

2/3

Ref. No. : M-4G6A

Revised: June 27, 2019

5. Fire-fighting measures

Suitable extinguishing media: Water spray, dry powder, CO₂ foam

<Note> The product is flame-retarded(self-extinguishing), but will burn, if continuously exposed to flame. Use the extinguishing media appropriate for the source of the fire. Self-contained breathing apparatus and personal protective equipment may be needed in the event of large fires.

6. Accidental release measures

Personal precautions : Avoid contact with the heated product. Gloves may be required to handle the product, when hot. If overheated, avoid breathing fumes which may be emitted.

Environmental precaution : In common with all good industrial practice, install in well ventilated areas only.

Methods for cleaning up : Sweep up and dump in a disposal container.

7. Handling and storage

Handling : No special handling advice required.

Storage : Store at room temperature in unopened packs to avoid direct sunlight.

8. Exposure controls/personal protection

Technical measures : Normal manufacturing environment.

Personal protection equipment : Under normal operation, not necessary.

Respiratory protection : Under normal operation, not necessary.

Hand protection : Gloves may be required to handle the product, when hot.

Eye protection : Under normal operation, not necessary.

Other protection : Under normal operation, not necessary.

9. Physical and chemical properties

Form : Solid(Tubing)

Color (standard) : Black.

Odor : Slight characteristic plastic odor

Melting point/range : The material has melting point, 140 ° C nominal, but it will not flow over the melting temperature due to the cross-linked structure.

Boiling point/range : Not applicable

Flash point : About 300 ° C

Ignition point : About 350 ° C

Explosive properties : Not applicable

Vapor pressure : Not applicable

Specific gravity(20 ° C): 1.4 nominal

Water solubility(20 ° C): Small molecular solubility in water

10. Stability and preparation

Stability : Stable at normal conditions. Recommended max. operating temperature is 150 ° C.

Do not heat over 300 ° C to avoid harmful vapors which may be formed at high temperatures.

Material to avoid : None

Hazardous decomposition products : None under normal conditions. If the product is overheated or burned, harmful vapors(e.g. carbon monoxide and hydrogen halides) may be generated.

SAFETY DATA SHEET

3/3

Ref. No. : M-4G6A

Revised: June 27, 2019

11. Toxicological information

Acute toxicity : Unknown
Skin : Not irritating, but the heated product has potential to cause thermal burn.
Eyes : If the product is overheated or burned, vapors may irritate eyes.
Inhalation : Harmful vapors produced by overheating or burning may cause irritation to the upper respiratory tract.
Ingestion : Not digestible.
Further information : During heating process of the product, slight plastic smell may cause discomfort for susceptible persons.

12. Ecological information

Biodegradability : Unknown(No data)
Aquatic toxicity : Unknown(No data)
Further information : Unknown(No data)

13. Disposal considerations

Product : Incinerate or bury in accordance with local and national regulations. Contact proper local authorities.
Contaminated packaging: Cardboard boxes and reels can be delivered to local recycling facilities.

14. Transport information

Not classified as dangerous with regard to the transport regulation.

15. Regulatory information

Poisonous and Deleterious Substances Control Law : N/A

California Proposition 65.  WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

16. Other information

SFP specification No. : RE4-G609

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or property assurances. The information relates only to the specific material designed and may not be valid for such a material used in combination with any other materials or in any process, unless specified in this text.