Ref. No. : SDS-E-4-14

Revised: May. 27, 22

1. Product identification

Product name : SUMITUBE A2				
Figuration: Plastic tube (This product is an Article. This product is not a chemical Substance or Mixture.)				
Recommended use of the product: Electrical insulation, etc.				
Restrictions on use: Other than the recommended use.				
Supplier : Sumitomo Electric Fine Polymer, Inc. (SFP)				
950,1-chome, Asashiro nishi, Kumatori-Cho, Sennan-Gun, Osaka, 590-0458, JAPAN				
(Tel) 072-452-7192, (Fax) 072-452-7195				
Emergency Tel. No.: For SFP subsidiary company				
Sumitomo Electric Interconnect Products, Inc.				
915 Armorlite Drive, San Marcos, CA 92069, U.S.A.				
(Tel) 760-761-0600, (Fax) 760-761-0620				
Sumitomo Electric Schrumpf-Produkte GmbH				
Oststrasse 89, D-22844 Norderstedt, Germany				
(Tel) 40-526-5010, (Fax) 40-526-4808				
Sumitomo Electric Fine Polymer (Suzhou) LTD.				
NO.232 Jinfeng Road, Suzhou New District, Suzhou, Jiangsu,215129				
(Tel) 0512-8918-6680, (Fax) 0512-8918-6686				
Sumi-Pac Corporation				
No.15, Kon Ye 5 Rd., Fon San Tsuen, Fu Kow Shan, Hsin Chu Hsien, Taiwan 30352, R.O.C.				
(Tel) 3-598-4165, (Fax) 3-598-4168				

2. Hazards identification

GHS classification Physical hazards: Not applicable Health hazards:Not applicable Environmental hazards:Not applicable Other hazards: If the product is overheated or burned, harmful vapors may be formed. The heated product has the potential to cause thermal burns, if touched. <Note> During heating process, a slight characteristic odor of plastic may be noticed. This odor is not harmful.

3. Composition/ Information on ingredients

Product type: Article Composition:

Substance name	CAS No.	Rate(wt%)
Crosslinked polyolefin	-	> 95
Other	Confidential	<5

4. First aid measures

Inhalation : If vapors from the burning or overheated product are inhaled, provide fresh air. If symptoms are not reduced, seek medical advice.

Skin contact: If the heated product contacts skin, remove the product immediately. If there is evidence of reddening or burn, seek medical advice.

Eye contact : If the heated product contacts eyes, rinse thoroughly with plenty of water for at least 15 minutes and seek medical advice.

Ingestion : Seek medical advice.

Revised: May. 27, 22

5. Fire-fighting measures

Recommended extinguishing methods: Suitable extinguishing media: Water spray, dry powder, CO₂ foam Fire extinguishing method that should be avoided: Specific hazards: Precautions for firefighters: To wear a protective mask

6. Accidental release measures

No risk at room temperature.

It can be recovered by hand.

Avoid contact with organic solvents to melt the polyolefin-based material.

7. Handling and storage

Handling :No special handling advice required.Storage :Store at room temperature in unopened packs to avoid direct sunlight.

8. Exposure controls/personal protection

Exposure limit values:	Without information. (In a normal state without the exposure.)
Personal protection equipment :	Under normal handling, not necessary.
Respiratory protection :	Under normal handling, not necessary.
Hand protection :	Gloves may be required to handle the product, when hot.
Eye protection :	Under normal handling, not necessary.
Other protection :	Under normal handling, not necessary.
During thermal contraction work:	Do the work wear heat-resistant gloves at the location of the local exhaust
	system.

9. Physical and chemical properties

Appearance(physical state,color):	Ttube (solid) , Color: Black, Yellow, Blue, Purple, White and Clear.
Upper/lower flammability or explosive limits:	No data
Odor:	Slight odor
Vapor pressure:	Not applicable
Odor threshold:	No data
Vapor density:	Not applicable
рН	Not applicable
Relative density	0.95 (20°C) (nominal)
Melting point/range :	The material has melting point, 110 $^{\circ}$ C nominal, but it will not flow over
	the melting temperature due to the cross-linked structure
Solubility(ies)	Small in water
Lnitial boiling point and range:	No data
Flash point:	300 °C (nominal)
Evaporation:	Not applicable
Flammability(solid,gas):	No data
Partition coefficient:n-octanol/water:	No data
Auto-ignition temperature:	350°C (nominal)
Decomposition t temperature and:	No data
Viscosity:	Not applicable

Revised: May. 27, 22

Pyrophoric gas:	It does not occur under normal handling
Asphyxiant:	Not applicable
Flammable dust:	It does not occur under normal handling

10. Stability and Reactivity

 Stability :
 Stable at normal conditions. Recommended max. operating temperature is 105° C.

 Do not heat over 300° C to avoid harmful vapors which may be formed at high temperatures.

 Material to avoid :
 None

 Hazardous decomposition
 None under normal conditions. If the product is overheated or burned, harmful vapors(e.g. carbon monoxide) may be generated.

11. Toxicological information

Acute toxicity :UnknownSkin :Not irritating, but the heated product has potential to cause thermal burn.Eyes :If the product is overheated or burned, vapors may irritate eyes.Inhalation :Harmful vapors produced by overheating or burning may cause irritation to the upper respiratory tract.Ingestion :None knownFurther information : During heating process of the product, slight plastic smell may cause discomfort for susceptible persons.

12. Ecological information

Biodegradability : None known Aquatic toxicity : None known Other environmental impact: None known.

13. Disposal considerations

Proper disposal container: Special container is not required.

Appropriate disposal methods: Please properly disposed of in accordance with local laws and regulations.

14. Transport information

Not classified as dangerous with regard to the transport regulation.

15. Regulatory information

Poisonous and Deleterious Substances Control Law : N/A

16. Other information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or property assurances. The information relates only to the specific material designed and may not be valid for such a material used in combination with any other materials or in any process, unless specified in this text.